

m²OMO a Vh LEVEL SENSOR DIESEL GLT 500 STANÉÍ

Product INTRODUCTION

GLT 500 is a Vhf/b Sonar • èN:gôl'm²OMmK'í_ SÑv,,N§TÁÿ 'Çu(šØSí—`xES—;_ S'R'O a VhO\N:S'R'eOa h8_Ãÿ ~í•çQh•êR"n)^i^e P•0 Sí• z ep[Wu5•íOíkcTŒOáS÷Œ t ý •“Qúh QÆv,j!bß'íb ep[WOá S÷0 GLT 500 T ^ W:Œ x ý T,SÖ[¢b7— IBÿ eág • T ^8% Äm²OMmK'ív,,• u(W^{3/4}iÿ N_g " "[ùyûR"•PvÑmKv,,^&xÁT8^§^{3/4}iÿ ná•³N T jåQµN v,,m²OMmK'íÿ N§TÁ•ý~í•ç|^{3/4}Ã^{3/4}i0 QCvhNö{[• 0 Vú[š]å ,zÿ • •çS(R)_a²s² € p^{1/2}0 s-Xfj!bßmK'Ö{le¹IÖÿ xnOÝkik>N§TÁz3 [šSí—`0

Features

- OSS ^{3/4}iÿ b—^rbp
- Y yí•“QúSí•
- Qhq c¥~Óg,,
- IP 6-2b
- xÁT8^§—2— ^{3/4}i
- qÄl'P"•PmK'í
- gôl'SÑu5g:~Äl'OMmK'í
- qÄl'l'•P•fm²OMmK'í
- qdwÿ0 l'u00 wóS {l

Specifications

GLT 50g/m ² OMSØ• Vh					
NāS÷	c¢Y4 {W				
A	^8%ÄY_b				
B	^&xAT8Y4				
NāS÷	'íz ý m Hqy				
X	0 ~ X jnkÖY, 0 - 1 m , 0 - 2 m , etc				
NāS÷	S(R) {W				
G	~hS				
A	~ÝS				
NāS÷	•“Qú				
E	4 - 2 0 mA				
K	0 . 5 - 4 . 5 V				
F	0 - 5 V				
J	0 - 1 0 V				
V	11 G(SR6y				
H	R S 4 G(SR6y				
NāS÷	Ou5				
V 1	1 2 - 3 0 V D C				
V 2	3 - 5 V D C				
V 3	5 V D C				
NāS÷	¾^l				
A 1	0 . 5 % F S				
A 2	0 . 2 5 % F SR6y				
NāS÷	~gP				
B 1	P U				
B 2	P T F E				
NāS÷	NÉ•(n)^l				
T 1	0! ý^5 0!				
T 2	0! ý^7 0!				
K	V 1	A 1	B 2	T 1	